

#### Description

1300 Coverall Semi-Gloss is a quality interior water-based production enamel which provides excellent scrubability and washability. 1300 Coverall Semi-Gloss can be applied over new or previously painted drywall, plaster and wood surfaces. For use on commercial, institutional and property management projects.

#### Recommended Uses

Previously painted or properly primed interior drywall, plaster, concrete, masonry and wood. Not recommended for wood cabinets or doors as blocking may occur.

#### Colors

White and custom pastel colors to order  
Bases: White & P

#### Packaging

One and five gallon containers

#### Finish

Semi-Gloss, sheen @ 60° = 64.0 - 68.0%

#### Surface Preparation

All contaminants that may impair adhesion should be removed. Glossy or slick surfaces must be scuff sanded and may require priming.

#### Primer

Drywall (New):	155 Seal Kote
Drywall (Existing):	4000 Uniprime
Concrete / Masonry:	4600 Uniprime II
Wood:	188 Acrylic Primer
	4200 Terminator II
	6600 AquaLac

#### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### Drying Time

Touch: 2 hours  
Recoat: 4 - 6 hours

#### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

#### Mil Thickness

Wet = 4.5                      Dry = 1.4

#### Thinning

Use at package consistency. If thinning is required, use water sparingly.

#### Composition

Titanium Dioxide	18.0%
Extenders	3.8%
<b>TOTAL PIGMENT</b>	<b>21.8%</b>
Vinyl Acrylic Resin	17.7%
Additives	10.3%
Water	50.2%
<b>TOTAL VEHICLE</b>	<b>78.2%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	31.0%
Solids by Weight:	43.7%
VOC:	44 g/l
Weight Per Gal:	10.2 lbs.
Viscosity:	94 - 98 KU

#### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.