

Exterior 100% Acrylic Flat Finish
Architectural Coating - Premium

Description

2200 Coverall Exterior Flat is a 100% acrylic for application on exterior tilt-up and masonry substrates. This product offers excellent alkaline resistance with a matte flat finish. It can also be used for wood siding and trim.

Recommended Uses

Tilt-ups, stucco, masonry, cmu and repaint of wood siding and trim.

Colors

White
Bases: A, D, & P

Packaging

One and five gallon containers

Finish

Flat, sheen @ 85° = 1.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded or chemically dulled prior to application of paint coatings and may require priming.

Primer

Stucco/Concrete/Masonry: 4600 Uniprime
4700 Tilt-Up Primer
Wood: 4200 Terminator II
Metal Non-Galvanized: 8600 Polytec Primer
9600 Protec Metal Prime
Metal Galvanized: 8600 Polytec Primer
4800 Metal Pro Primer
Aluminum: 8600 Polytec Primer

Application

Brush, roll or spray. Ambient and surface temperatures must be above 40F and relative humidity below 80%. Do not apply when air or surface temperature may drop below 35F within 48 hours.

Drying Time

Touch: 1 hour
Recoat: 3 hours

Coverage

Up to 325 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 5.0 Dry = 1.7

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	13.5%
Extenders	25.1%
TOTAL PIGMENT	38.6%
Acrylic Resin	11.2%
Additives	3.6%
Water	46.6%
TOTAL VEHICLE	61.4%

Weights & Measurements +/-3.0%

Solids by Volume:	34.2%
Solids by Weight:	51.5%
VOC:	46 g/l
Weight Per Gal:	11.3 lbs.
Viscosity:	98 - 102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.
MPI - #10



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

Updated 08.2024

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

