

Exterior 100% Acrylic Flat Finish  
Architectural Coating - Premium

### Description

Acriglo Exterior Flat is a premium 100% acrylic finish for use on properly primed wood, concrete, masonry, stucco and metal. Provides a tough, flexible matte flat finish with outstanding resistance to chalking and fading. An excellent choice for commercial, institutional, property management and new home construction projects.

### Recommended Uses

New or previously painted wood. Properly primed concrete, stucco, masonry, smooth wood and metal.

### Colors

White and custom colors to order.  
Bases: A, D, & P

### Packaging

One and five gallon containers

### Finish

Flat, sheen @ 85° = 0.9 - 1.3%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primer

Concrete / Masonry:	4600 Uniprime II
Cedar / Redwood:	4000 Uniprime
Metal Non-Galvanized:	8600 Polytec Primer
	9600 Protec Metal Prime
Metal Galvanized:	4800 Metal Pro Primer
	8600 Polytec Primer

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch: 1 hour  
Recoat: 4 - 6 hours

### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 4.0      Dry = 1.7

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	14.1%
Extenders	29.9%
<b>TOTAL PIGMENT</b>	<b>44.0%</b>
Acrylic Resin	13.4%
Additives	5.1%
Water	37.5%
<b>TOTAL VEHICLE</b>	<b>56.0%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	42.0%
Solids by Weight:	58.0%
VOC:	45 g/l
Weight Per Gal:	11.8 lbs.
Viscosity:	98 - 102 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.  
**MPI** - #10



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

04.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

