



Exterior 100% Acrylic Finish  
**FOR USE IN STATES OF NEVADA & ARIZONA ONLY**  
 Architectural Coating - Specialty

2800AF Coverall Concrete Coating Exterior 100% Acrylic Finish

Physical Properties - Table 1

Property	Value	Method
Solids by Weight	58%	ASTM D 2369
Solids by Volume	42%	ASTM D 2697
Weight per Gallon	11.72 lbs	ASTM D 1475
Viscosity	1500 - 1800 @ 70°F	ASTM D 2196
Dry Time	1 hour	ASTM D 1640
Cure Time	4 - 6 hours	ASTM D 1640
Gloss	<10 gloss units @ 60°	ASTM D 523
Permeability	8.8 perm	ASTM D 1653, Method A
Adhesion to Concrete / Masonry	732 lbs / sq. in.	ASTM D 7234

Performance Properties - Table 2

Property	Value	Method
Resistance to Accelerated Weathering	Color Retention & Ultraviolet Resistance After 3,000 Hours Continuous Exposure In QUV Cabinet As Per ASTM G 154	No Deleterious Effects. No Chalking or Flaking As Per ASTM D 659, replaced by D4214.
Resistance To Natural Sunlight (2 Years)	Color & Gloss Retention After 18,000 Megalous Of Radiation Exposure As Per ASTM G 90	Color & Gloss Changes Less Than 1 CJE Unit
Resistance To Wind Driven Rain	ASTM D 6904	0 penetration after 24 hours @5 inches of water pressure
Resistance To Salt Spray. Note: Previously This Was 3,000 Hours	ASTM B 117	No Deleterious Effects; No Color Fade After 500 Hours
Abrasion Resistance	ASTM D 968	15.5 L/Mil

04.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

