

Zero\* V.O.C Interior Latex Low Sheen  
Architectural Coating - Quality

### Description

V-PRO 300 (320 Velvasheen) is a zero\* VOC, interior professional grade latex velvasheen for use on properly primed walls and ceilings including masonry, plaster, concrete, acoustic, wood and metal surfaces. This product also offers good washability and minimizes wall imperfections.

### Recommended Uses

Designed for the repaint maintenance and housing residential markets where a low sheen finish is desired.

### Colors

Tintable White

### Packaging

Five gallon containers

### Finish

Velvasheen, sheen @ 60° = 7.0 - 9.0%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primer

Masonry / Concrete:	V-PRO 301 Primer
Drywall (New):	V-PRO 301 Primer
Drywall (Existing):	4000 Uniprime
	8000 Carefree Prime-ZALL
Wood:	4000 Uniprime
	8000 Carefree Prime-ZALL
Metal:	9600 Protec Metal Prime
Glossy Surfaces:	4000 Uniprime

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

### Drying Time

Touch:	1 hour
Recoat:	4 hours

### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 4.0                      Dry = 1.5

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	13.0%
Extenders	17.0%
<b>TOTAL PIGMENT</b>	<b>30.0%</b>
Vinyl Acrylic	13.5%
Additives	5.8%
Water	50.7%
<b>TOTAL VEHICLE</b>	<b>70.0%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	30.5%
Solids by Weight:	45.4%
VOC:	<2 g/l
Weight Per Gal:	10.6 lbs.
Viscosity:	96 - 102 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.

\*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

\*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

