

Scuff Resistant Paint with a Smooth Silk-Like Finish Architectural Coating - Premium Plus

Description

SCUFF-TEC PAINT (Matte Silk Finish) is an intricately crafted, premium plus, interior / exterior paint featuring Scuff-Resistant Technology that makes it washable, stain and scuff resistant, with a smooth silk like finish. Scuff-Resistant Technology is a combination of high-performance acrylic urethane cross-polymer technologies, which provides excellent durability, with an unique innovation in pigment chemistry to create an extremely tough and resistance surface but with a silk like softness. **SCUFF-TEC PAINT (Matte Silk Finish)** can be used as a *paint-and-primer in one, has excellent wash and scrub properties, resistant to household and light industrial chemicals, quick dry, great touch-up, easy application, and is spatter resistant. Environmentally friendly with low VOC <50 g/l, low odor, NON-EG Certified, with anti-microbial properties.

Recommended Uses

SCUFF-TEC PAINT (Matte Silk Finish) is ideal for interior and exterior use on premier custom residential and commercial projects. This includes high-traffic areas in schools, hotels, hospitals, retail spaces, restaurants, gym locker rooms, cafeterias, USDA inspected facilities, restrooms, stairwells, cabinets and any surfaces that require a paint with scuff and burnish resistance, and a desired smooth silk like finish.

Colors

White

Bases: H, M, D, and A

Packaging

One and five gallon containers

Finish

Matte, sheen @ 60° = 3.0 (+/-1%)

Surface Preparation

Proper preparation is essential to the performance of water-based coatings. Remove oil, grease, dirt, loose rust, loose peeling paint or other contaminants that may impair adhesion and affect performance. Glossy or slick surfaces should be lightly sanded. For caulking use Vista 55-year caulk.

Primer

| | |
|--------------------------|---|
| Plaster/Drywall: | 8000 Carefree Prime-ZALL 4000 Uniprime |
| Concrete/Masonry: | 4600 Uniprime II 8000 Carefree Prime-ZALL |
| New Wood (Interior): | 6600 Aqua Lac 8000 Carefree Prime-ZALL |
| Repaint Wood (Interior): | 8600 Polytec Primer 8000 Carefree Prime-ZALL |
| Wood (Exterior): | 4000 Uniprime 8000 Carefree Prime-ZALL |
| Metal Non-Galvanized: | 8600 Polytec Primer 9600 Protec Metal Prime |
| Metal Galvanized: | 8600 Polytec Primer 4800 Metal Pro Primer |
| Aluminum: | 8600 Polytec Primer |

Application

Brush, roll or spray. Ambient and surface temperatures must be above 40F and relative humidity below 80%. Do not apply when air or surface temperature may drop below 35F within 48 hours.

Drying Time

Touch: 1 hour
Recoat: 4 hours

Coverage

300 - 350 square feet per gallon, depending on porosity and texture of the surface.

Thickness

Wet = 5.0 mil Dry = 2.0 - 2.5 mil

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

| | |
|----------------------|--------------|
| Titanium Dioxide | 22% |
| Extenders | 15.7% |
| TOTAL PIGMENT | 37.7% |
| Proprietary Resins | 15.2% |
| Additives / Solvents | 5.0% |
| Water | 42.2% |
| TOTAL VEHICLE | 62.3% |

Weights & Measurements +/-3.0%

| | |
|-------------------|--------------|
| Solids by Volume: | 39% |
| Solids by Weight: | 53% |
| VOC: | <50 g/l |
| Weight Per Gal: | 11.54 lbs. |
| Viscosity: | 100 - 105 KU |

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.
Meet MPI - Sheen Level 1



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Scuff Resistant Technology is a proprietary combination of high-performance acrylic urethane cross-polymer technologies, which provides excellent durability, with an unique innovation in pigment chemistry to create an extremely tough and resistance surface but with softness of silk.

Last Updated 04.2024

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.